

No.1 POCKET KODAK Series II



Serial Nr.: 27457
Lens Nr.: 10820

Characteristics and functions

Camera Folding, the N.1 Pocket Kodak Series II uses Roll-film type 120 films and provides 6x9cm images. (2 ¼ "x 3 ¼"). The No. 1 Poket Kodak was produced between 1922 and 1931. All Kodak Pocket cameras have the door to use the 120 'Autograph' Roll-Film films produced by Kodak between 1914 and 1934.

This camera mounts a lens Anastigmat 108mm./ f.7, 7. The "Diomatic 0" shutter has six settings: B, T 1/10 1/25 1/50 and 1 / 100s. that are set by turning the small wheel with the small metal arrow as a reference. The cursor below the lens allows you to select the correct exposure time according to the set aperture and ambient light conditions: very cloudy, cloudy, hazy sun and bright sun. To open the bellows door it is sufficient to raise the chromed lever - which also serves as a support foot - and, raise the side levers. The chrome-plated lever on the left serves to arm the shutter,

the one on the right for shooting. The magnifying viewfinder can be rotated 90 ° for shooting with a horizontal camera. There are two holes for using the tripod: one is located on the base of the camera, the other is on the bellows door and is used for vertical camera shooting.

Weight 480g.

Length 168mm. Height 85mm. Thickness 33mm. (closed), 136mm. (open).

Technical Specifications

Film Type:	Roll-Film 120 (autograph) Images: 6 x 9cm. (2 ¼" x 3 ¼").
Shutter:	Diomatic 0 – Central, Mechanical.
Meter:	No
Diaphragms:	f/7.7, f/11, f/16, f/22, f/32
Times:	1/10", 1/25", 1/50", 1/100", B, T
Lens:	Kodak Anagstigmat f/7.7 / 108mm.
Flash:	No.
Focusing:	From 1.5mt. to infinity (1,5; 2; 2,5; 3; 4; 5; 15; 30)
Characteristic:	Black metal body and black leather.
Accessories:	Leather carry handle. Threaded hole for stand (2). Openable section for Autograph system.

