

LEITZ PRADOVIT 253 DU



Type 031.206.010

Characteristics and functions

Autofocus automatic projector with structure in high-strength plastic with a brown / ivory-colored corrugated surface, uses LKM type loaders of 60 or 80 slides or, alternatively, standard loaders of 36 or 50 slides mounted in 5x5cm frames.

Standard lens supplied: Leitz-Colorplan 1: 2.5 / 90.

Optional Leitz lenses are also available:

ELMATIT-P 2,8/50 mm

ELMARON 2,8/85 mm

COLORPLAN-CF 2,5/90 mm

ELMARON 2,8/120 mm

ELMARON 3,2/150 mm

During projection there is a high illumination of the slide thanks to the use of 24V / 250W halogen lamps. The PRADOVIT 253 DU also has a 110 / 240V / 50-60Hz voltage selector. The forced ventilation allows an excellent cooling of the lamp during the projection phase.

The remote control (with cable) allows the slide to be forwarded / returned, manual adjustment of the focus - useful when using slides mounted in frames without glass, which tend to sag under the effect of the heat of the lamp; furthermore there is the possibility of projecting a luminous index - useful in conferences.

It is possible to use the built-in timer from 3 to 30 seconds interval, which allows a fully automatic projection

The PRADOVIT 253 DU is equipped with two adjustable front feet to obtain in perfect horizontal alignment and a vertical drawer that allows the slide to be extracted in projection - indispensable when a slide is positioned incorrectly in the loader (for example: in projection we have the sky below and the earth above!).

Slide projector with built-in Triac that allows the use of two LEITZ PRADOVIT 253 DU projectors in combination with the LEITZ DU-24 A cross-fade control unit. In this case the projection is fluid, without the annoying "black screen" during the transition from one slide to the other.

Using the automatic command for fading D.U.-24 A for two projectors you have the possibility of recording on tape to make the projection completely automatic.