

MINOLTA POWER GRIP 2 SET 1982



Serial Nr. no
Minolta Code 8808-703

Characteristics and Functions

Evolution of the Power Grip presented in 1979, the Minolta Power Grip 2 allows the use of the new electronic flashes "Auto Electroflash PX" (360PX, 280PX and Macro 80PX) in combination with the X-700 presented in 1981. With the Power Grip 2 they are all those devices that have the three-contact socket on the front of the flash foot can be used as well as the previous Auto Electroflash 320X and 320. The OC cable (Cable OC) is standard and allows you to connect the camera's hot shoe with the handle via the Cable OC Terminal located on the rear of the handle. Optional cables are also available such as: the MD cable to connect the Motor Drive 1 to the handle, the AW cable to connect the Auto Winder G or D to the handle via the Cable MD / Cable AW Terminal located on the left side of the handle and the FB cable to connect the Multi Function Back

to the handle using the Cable FB Terminal located at the rear, at the bottom of the Power Grip 2. Finally, the EX extension cables, which can be used up to a maximum of five, allow for greater distances the grip from the camera. Power is supplied by six 1.5v type AA batteries that are to be used in the Battery Cartridge PG supplied with the device. The Battery Cartridge PG is located in the foot of the handle: to remove it, you need to move the slider located on the base cover. The Minolta Power Grip 2 can work with 1.2v Nickel-Cadmium (Ni-Cd) rechargeable batteries, or with 1.5v Alkaline-Manganese (AM) batteries, or with 1-liter zinc-carbon batteries., 5v. Weight of the handle complete with bracket and battery holder (excluding batteries) 530g. Length 215mm., Height 226mm., Depth 90mm. when the Camera Bracket 2 is correctly mounted in the Power Grip 2.

