

# POLAROID Land Camera Model AUTOMATIC 440



|                              |  |
|------------------------------|--|
| <b>Year of construction:</b> | 1971-1976  |
| <b>Film type:</b>            | 107 (B/W) – 108 (Color)  |
| <b>Shutter:</b>              | Electronic - Aperture-priority automatic exposure only   |
| <b>Meter:</b>                | CdS  |
| <b>Diaphragm:</b>            | From f/8.8 to f/42   |
| <b>Times:</b>                | From 10sec. to 1/200sec  |
| <b>Lens:</b>                 | 114mm f/8.8 3-elements (glass)   |
| <b>Synchronisation:</b>      | Has PC socket for flash; flashgun is clipped to the top of the camera.   |
| <b>Self-timer:</b>           | No   |
| <b>Focusing:</b>             | Unit focus; focus is controlled by pushing on either side of a sliding arm located near the base of the bellows struts.  |
| <b>Characteristics:</b>      | Separate window view/rangefinder assembly.<br>Viewfinder has projected frame-lines and automatic parallax compensation.<br>Settings for film speeds of 75, 150, 300, and 3000 ASA.<br>Exposure compensation dial with range of -1/+2 stops ("Lighten/Darken" control). |
| <b>Accessories:</b>          | Nylon carrying strap.<br>Built-in mechanical development timer   |
| <b>Note:</b>                 | -  |
| <b>Estimated Production:</b> | 340,000 – 500,000  |