

# POLAROID VISION



Serial Nr. E3K\*E722NBFA

## Characteristics and functions

The Polaroid brand is linked to a revolutionary chemical process experimented in 1929 by Dr. Edwin Land who used a support that already contained within it the chemical reagents necessary for the development of the image. In 1947 the first Polaroid camera was born, through which photographs could be obtained in a few seconds after the shot. Due to its ease of use, the Polaroid system was a huge success, even if the print quality never reached the level of traditional photo printing.

The Polaroid Vision uses the new Polaroid Vision 95 films (600/29° ISO) for color photographs. These films are "self-developing" like the previous SX-70 / 600. Each charger is for 10 shots.

With the Polaroid Vision you get color images 2.87in. x 2.17in.. on waterproof cardboard of 4.37in. x 2.52in.

The camera is Auto Focus SLR type. The lens focuses from 4 feet to infinity.

This camera has a built-in CdS meter.

The appliance has a built-in electronic flash with automatic intervention ("Light Dose" Sistem).

The power supply for the camera and flash operation is supplied by the battery inserted in the film container.

Weight 22.51oz. belt included.

Width 7.01in.

Height 3.74in. (closed) / 4.13in. (open).

Depth 2.05in. (closed) / 4.33in. (open)

## Technical Specifications

Film Type:	Polaroid Vision 95
Shutter:	Electronic
Meter:	CdS
Diaphragm:	From f/12 to f/72
Times:	-
Lens:	107mm f/12 - 3-element, with front lens in anti-reflective optical glass
Flash:	Built in Electronic Flash (Flash range from 2 to 10 feet)
Self-timer:	Yes – 12" of delay from the click
Focusing:	Bizonal focus from 2 feet to Infinity
Characteristics:	Acoustic signals for 'empty loader', 'photo collection compartment is full', 'locked photo' and 'self-timer activated'. Light signals: 'flash lock / flash ready' (red / green) and 'self-timer' (red - on the front). slider for brightness control: +/- ¾ diaphragm
Accessories:	Nylon strap. Leatherette case.