

**BRUMM n° 131-03 – LANCIA AURELIA B 24 – 1956-58
CONVERTIBILE – aperta**



BRUMM n° 131-03 – LANCIA AURELIA B 24 – 1956-58 CONVERTIBILE – aperta

Modellino: Colore alluminio metallizzato. Paraurti, maniglie, calandra, cornici fari e specchio cromati. Guida a sinistra. Parabrezza con deflettori. Interni e volane neri. Capote aperta. Cerchi-ruota color argento metallizzato con coppe cromate e coperture in gomma nera. Targa posteriore: MI 223412. Fondello in metallo nero. Scala 1:43. Con scatola originale.

Nota: variante 03 di colore a catalogo.

Model: *Metallic aluminum color. Chrome bumpers, handles, grille, headlight frames and mirror. Drive left. Windshield with deflectors. Black interior and flywheels. Hood open. Metallic silver wheel rims with chrome cups and black rubber covers. Rear number plate: MI 223412. Black metal caseback.*

1:43 scale. With original box.

Note: *color variant 03 in the catalog.*

LANCIA AURELIA B 24 CONVERTIBILE – 1956-58

Motore tipo B24 6 cilindri a V di 60°, 2451cc. (alesaggio 78 x corsa 88,5mm.), 110cv. a 5300 giri al minuto. Distribuzione a valvole in testa, 1 albero a camme centrale in testa. Alimentazione con 1 carburatore Weber. Lubrificazione forzata. Trasmissione: ruote motrici posteriori. Frizione monodisco a secco. Cambio a 4 marce + retromarcia con leva centrale. Sospensioni anteriori a ruote indipendenti, molle elicoidali. Sospensioni posteriore ad assale rigido e balestre longitudinali. Sterzo a vite e settore. Freni: a pedale impianto idraulico con 4 freni a tamburo; a mano meccanico sulle ruote posteriori. Ruote in lamiera stampata. Pneumatici 165x400. Impianto elettrico a 12v. Struttura: scocca portante in lamiera d'acciaio. Carrozzeria spider 2 porte, 2 posti. Possibilità di adattare l'hard top. Passo 2450mm. Carreggiata anteriore 1290mm., posteriore 1300mm. Lunghezza 4200mm. Larghezza 1555mm. Altezza 1305mm. Peso in ordine di marcia 1115kg. con la capote di tela. Velocità Massima 185Km./h. Consumo medio 12,7lt x 100Km. - 7,9Km./lt. Dati di produzione: numero iniziale 1001. Unità prodotte 240. Carrozzeria Pininfarina. Lancia produce vetture con guida a destra di serie fino al 1955; la guida a sinistra è a richiesta, mentre dal 1956 diventa la guida standard.

Engine type B24 6 cylinders to V of 60 °, 2451cc. (bore 78 x stroke 88.5mm.), 110cv. at 5300 revolutions per minute. Overhead valve timing, 1 central overhead camshaft. Powered by 1 Weber carburettor. Forced lubrication. Transmission: rear drive wheels. Dry single plate clutch.

4-speed gearbox + reverse with central lever.

Front suspension with independent wheels, coil springs.

Rear suspension with rigid axle and longitudinal leaf springs.

Screw and sector steering. Brakes: foot operated hydraulic system with 4 drum brakes; mechanical hand on rear wheels. Wheels in pressed sheet metal. 165x400 tires.

12v electrical system. Structure: supporting body in sheet steel.

2-door, 2-seater spider body. Possibility to adapt the hard top. Wheelbase 2450mm.

Front track 1290mm., Rear 1300mm. Length 4200mm. Width 1555mm.

Height 1305mm. Curb weight 1115kg. with the canvas hood. Maximum speed 185Km./h.

Average consumption 12.7lt x 100Km. - 7,9Km./Lt.

Production data: starting number 1001. Units produced 240. Pininfarina bodywork.

Lancia produced right-hand drive cars as standard until 1955; the left-hand drive is on request, while from 1956 it becomes the standard drive.